

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

19



Europäisches Patentamt
European Patent Office
Office européen des brevets



11 Publication number:

0 542 238 B1

12

EUROPEAN PATENT SPECIFICATION

49 Date of publication of patent specification: 12.04.95 51 Int. Cl.⁸: B62M 3/08

21 Application number: 92119306.6

22 Date of filing: 11.11.92

54 Bicycle cleat coupling structure.

30 Priority: 13.11.91 JP 296159/91

43 Date of publication of application:
19.05.93 Bulletin 93/20

45 Publication of the grant of the patent:
12.04.95 Bulletin 95/15

84 Designated Contracting States:
DE FR GB IT

56 References cited:
EP-A- 0 393 585
EP-A- 0 428 140
US-A- 5 142 938

73 Proprietor: SHIMANO INC.
77, 3-cho Olmatsu-cho
Sakai-shi
Osaka (JP)

72 Inventor: Nagano, Masashi
74-19, Midorigaoka
Izumi-shi,
Osaka (JP)

74 Representative: Säger, Manfred, Dipl.-Ing.
Postfach 506
CH-9004 St. Gallen (CH)

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid (Art. 99(1) European patent convention).

Description

BACKGROUND OF THE INVENTION

FIELD OF THE INVENTION

The present invention relates to a structure for coupling a cleat to a bicycle pedal.

DESCRIPTION OF THE PRIOR ART

Various structures have heretofore been used for coupling cleats to bicycle pedals. Many of these structures are designed to fix shoes to pedals. The shoes tend to move axially of the pedals with leg action during cycling. However, such coupling structures do not allow the shoes to move axially of the pedals, resulting in an additional burden imposed on the rider's legs.

Fig. 4 shows a device developed in view of the above drawback. This drawing shows clamping projections 3 and 4 formed on a pair of cleat clamps of a pedal for securing a cleat to the pedal. References 5a and 5b denote engaging projections of the cleat 5 shown in Fig. 1. A pedal axis is referenced X in Fig. 4. This device allows the cleat 5 to oscillate freely about a point of contact Z between the projection 5a of the cleat 5 and the clamping projection 3. Thus, the rear projection 5b of the cleat 5 is displaceable relative to the clamping projection 4.

With this prior structure, a treading force of the rider's foot is applied to the pedal at a point F in Fig. 4. This point F is relatively long distance away from the point Z about which the cleat 5 is oscillatable. This results in an inconvenience that, when the cleat 5 oscillates to a large extent, the cleat 5 would readily slip off the pedal by momentum.

SUMMARY OF THE INVENTION

An object of the present invention is to provide a structure for coupling a cleat of a rider's shoe to a bicycle pedal, which coupling structure allows the cleat to oscillate horizontally relative to the pedal about a rearward position of the cleat.

The above object is fulfilled, according to the present invention, by an apparatus for coupling a cleat comprising a pedal shaft for rotatably supporting a pedal, a tread surface extending parallel to the pedal shaft for contacting a bottom of a shoe, a first pivotal axis provided on the pedal, and a rear cleat clamp pivotable about the first pivotal axis. The rear cleat clamp includes a cleat engaging device for engaging one end of the cleat until a force exceeding a predetermined value is applied thereto.

This apparatus further comprises a front cleat clamp opposed to the rear cleat clamp across the pedal shaft, and a pair of restrictor projections disposed between the second cleat clamp and the pedal shaft for restricting displacement of the cleat. The front cleat clamp cooperates with the rear cleat clamp to couple the cleat to the pedal. The restrictor projections are spaced apart from each other by a distance greater than a width along the pedal shaft of a portion of the cleat for contacting the restrictor projections. Thus, the cleat is allowed to oscillate freely on the tread surface through the distance between the restrictor projections and about the cleat engaging device.

As noted above, one end of the cleat is engageable with the cleat engaging device provided for the rear cleat clamp for securing the cleat to the pedal. This cleat engaging device and the pair of restrictor projections allow the cleat to oscillate freely about the cleat engaging device. According to the invention, the rider's leg is allowed to move along the pedal shaft to lighten the burden falling on the leg. Further, a point at which a treading force is transmitted from the rider's foot to the pedal is at a reduced distance to the center of the cleat oscillation. This allows free oscillations of the cleat with little momentum, to minimize the possibility of the cleat inadvertently becoming disengaged from the pedal.

Features and effects of the invention will become more apparent from the following more detailed description of the embodiment of the invention taken with reference to the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a perspective view of a cleat attached to a shoe, and a pedal having a cleat coupling mechanism according to the present invention, Fig. 2 is a side view showing engagement between the pedal and cleat shown in Fig. 1,

Fig. 3 is a plan view of the cleat coupling mechanism according to the present invention, with unnecessary parts omitted for convenience of illustration, and

Fig. 4 is a plan view of a known cleat coupling mechanism.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

An embodiment of the present invention will be described next with reference to the drawings.

Fig. 1 shows a bicycle pedal P having a coupling mechanism for coupling a cleat 5. The pedal P includes a pedal body 1 rotatably supported on a pedal shaft 2 fixed to a crank arm C. A cycling

shoe S is attached to the pedal P through the cleat 5.

The cleat coupling mechanism will be described next. The pedal P defines a tread surface 1a for contacting the shoe S. The tread surface 1a is provided by a contact plate 8 fixed in place by screws. The pedal P further includes a rear cleat clamp 7 mounted on a support arm 7a to be pivotable about an axis Y extending parallel to the pedal shaft 2.

The rear cleat clamp 7 includes a cleat clamping projection 4 extending substantially parallel to the tread surface 1a. The clamping projection 4 has a recess 4a for engaging a rear end projection 5b of the cleat 5. Though not shown, the rear cleat clamp 7 is biased by a lock spring in a direction to engage the cleat 5.

Similarly, a front cleat clamp 6 is supported to be pivotable about an axis (not shown) extending parallel to the pedal shaft 2, and biased by a lock spring (not shown) in a direction to engage the cleat 5. The front cleat clamp 6 also has a cleat clamping projection 3 extending parallel to the tread surface 1a and toward the rear cleat clamp 7.

The contact plate 8 includes front restrictor projections 8a and 8b and rear restrictor projections 8c and 8d for restricting movement parallel to the contact plate 8 of the cleat 5 engaged with the pedal P. As seen from Fig. 1, the front restrictor projections 8a and 8b extend substantially perpendicular to the tread surface 1a, and diverge outwardly of the pedal P toward the rear cleat clamp 7. The rear restrictor projections 8c and 8d extend outwardly of the pedal P and away from the contact plate 8.

As seen from Fig. 2, the pedal P in this embodiment has a further pair of front cleat clamp 6 and rear cleat clamp 7 on an opposite surface.

How the cleat 5 is coupled to the cleat coupling mechanism will be described next. As shown in Fig. 1, the cleat 5 includes a projection 5a for engaging the front cleat clamp 6, and the projection 5b for engaging the rear cleat clamp 7. First, the rider inclines the shoe S to place the tip of the shoe lower than its heel (not shown), and thus the projection 5a lower than the projection 5b. Next, the projection 5a is inserted between the contact plate 8 and front cleat clamping projection 3. The front restrictor projections 8a and 8b act as guides at this time. The rider presses the cleat 5 toward the tread surface 1a with the projection 5a of the cleat 5 inserted between the contact plate 8 and front cleat clamping projection 3. This causes the rear cleat clamp 7 to pivot about the axis Y against the biasing force of the lock spring, whereby the projection 5b of the cleat 5 is inserted between the contact plate 8 and rear clamping projection 4.

The front clamping projection 3, under the biasing force of the lock spring of the front cleat clamp 6, presses the projection 5a of the cleat 5 on the contact plate 8. Similarly, the rear clamping projection 4, under the biasing force of the lock spring of the rear cleat clamp 7, presses the projection 5b of the cleat 5 on the contact plate 8. Thus, the cleat 5 is attached to the pedal P. In this state, the restrictor projections 8a and 8b restrict free displacement of the cleat 5 in fore and aft directions. Consequently, the restrictor projections 8a and 8b prevent the cleat 5 from pushing and oscillating the front cleat clamp 6 to become disengaged from the pedal P.

When releasing the cleat 5 from the pedal P, the rider turns the shoe S until the projection 5a of the cleat 5 contacts the restrictor projection 8a or 8b. Then, the rider exerts a force exceeding a predetermined value to twist the shoe S about an axis substantially perpendicular to the contact plate 8 on the pedal P, using a point of contact between the projection 5a and restrictor projection 8a or 8b as a fulcrum point. This results in the projection 5b disengaging from the recess 4a. Then, the rear cleat clamp 7 pivots in a release direction against the biasing force of the lock spring (not shown), thereby releasing the cleat 5 from the pedal P. The rear restrictor projections 8c and 8d act as guides at this time to facilitate release of the cleat 5 by raising the cleat 5 from the tread surface 1a with turning of the cleat 5.

As seen from Fig. 3, the front restrictor projections 8a and 8b are spaced apart from each other by a width W which is larger than a width H of the projection 5a of the cleat 5. Thus, the projection 5a is displaceable sideways relative to the pedal P even when the cleat 5 is attached to the pedal P. The projection 5b of the cleat 5 has an extreme end 5c thereof engageable with the recess 4a defined in the rear clamping projection 4. Strictly speaking, therefore, the displacement of the cleat 5 is its oscillation about a point of contact Z between the extreme end 5c and the rear clamping projection 4. Reference M in Fig. 3 denotes a centerline of the cleat 5. This centerline M has a degree of freedom through an angle indicated by "A".

When the rider pedals the bicycle, the shoe S is allowed to move along the pedal shaft as the pedal P moves relative to a bicycle frame. Thus, the rider's leg is free from an extra burden.

Fig. 4 shows a conventional cleat coupling mechanism which also allows oscillations of the cleat. However, the oscillations are made about the point of contact Z between the front clamping projection 3 and the projection 5a of the cleat 5. The treading force of the rider's foot is applied to the pedal at the point F in Fig. 4. Since the point F is a relatively long distance away from the point Z

about which the cleat 5 is oscillatable, the cleat 5 tends to slip off the pedal by momentum when oscillated to a large extent.

In the construction according to the present invention on the other hand, the point F has a short distance L to the point Z about which the cleat 5 is oscillatable as shown in Fig. 3. Although the degree of freedom provided for the cleat 5 is comparable to that of the prior art shown in Fig. 4, the movement of the cleat 5 involves little momentum, and hence a reduced chance of becoming disengaged from the pedal. Further, the oscillations about the point Z result in relatively minor variations in the distance of the point F to the pedal axis X. This in turn results in little change in the transmission rate of the treading force from the rider's foot to the pedal shaft 2.

In the foregoing embodiment, the cleat 5 is oscillatable about the point Z provided by the recess 4a in the clamping projection 4. This recess may have a width to allow the projection 5b of the cleat 5 to move freely relative to the clamping projection 4 along the axis X.

A plurality of cleats having varied widths H may be provided to make different degrees of cleat oscillations available. The restrictor projections 8a and 8b may be positionally adjustable to enable selection of a degree of cleat oscillations.

The cleat 5 may be adapted oscillatable relative to the shoe rather than the pedal. Further, the cleat clamps 6 and 7 may be constructed oscillatable relative to the pedal body, with the cleat 5 and shoe S fixed to the cleat clamps 6 and 7.

Claims

1. An apparatus for coupling a shoe having a cleat (5) to a bicycle pedal (1), comprising:
 - a pedal shaft (2) for rotatably supporting said pedal;
 - a tread surface (1a) extending parallel to said pedal shaft for contacting a bottom of said shoe;
 - a first pivotal axis (Y) provided on said pedal;
 - a rear cleat clamp (7) pivotable about said first pivotal axis (Y), and including cleat engaging means (4) for engaging one end (5b) of said cleat (5) until a force exceeding a predetermined value is applied thereto;
 - a front cleat clamp (6) opposed to said rear cleat clamp (7) across said pedal shaft (2), said front cleat clamp (6) being cooperative with said rear cleat clamp (7) to couple said cleat (5) to said pedal (2); and
 - a pair of restrictor projections (8a,8b) disposed between said front cleat clamp (6) and said pedal shaft for restricting displacement of

said cleat;

characterized in that

said restrictor projections (8a,8b) are spaced apart by a distance (W) greater than a width (H) along said pedal shaft of a portion (5a) of said cleat (5) for contacting said restrictor projections (8a,8b), thereby allowing said cleat to oscillate freely on said tread surface (1a) through said distance between said restrictor projections and about the cleat engaging means (3) of the front cleat clamp (6).

2. An apparatus according to Claim 1 characterized in that said pedal further includes a second pivotal axis opposed to said first pivotal axis across said pedal shaft, said front cleat clamp being pivotable about said second pivotal axis.
3. An apparatus according to Claim 1 or 2 characterized in that said restrictor projections extend substantially perpendicular to said tread surface.
4. An apparatus according to one of Claims 1 to 3 characterized in that said first and second pivotal axes extend parallel to said pedal shaft.
5. An apparatus according to one of Claims 1 to 4 characterized in that said cleat engaging means is in a form of a recess defined in said first cleat clamp for engaging said cleat.
6. An apparatus according to Claim 5, characterized in that said rear cleat clamp includes a first clamping projection extending substantially parallel to said tread surface toward said front cleat clamp and defining said recess, and said front cleat clamp includes a second clamping projection extending substantially parallel to said tread surface toward said rear cleat clamp, said first clamping projection and said second clamping projection being restricted against movement away from said tread surface, thereby to couple said cleat to said pedal.
7. An apparatus according to one of Claims 1 to 6 characterized in that said restrictor projections are aligned symmetric about a centerline extending perpendicular to said pedal shaft and included in said tread surface, said restrictor projections diverging away from said centerline as said restrictor projections extend toward said front cleat clamp.
8. An apparatus according to one of Claims 1 to 7 characterized in that said rear and front cleat

clamps are spring-loaded in directions to engage said cleat.

9. An apparatus according to one of Claims 1 to 8 characterized in that said restrictor projections are arranged to restrict free movement of said cleat along a centerline extending perpendicular to said pedal shaft and included in said tread surface.

Patentansprüche

1. Anordnung zum Ankoppeln eines Schuhs mit Stoßplatte (5) an einem Fahrradpedal (1), welche folgendes aufweist:
 - eine Pedalwelle (2) zur drehbaren Abstützung des Pedals;
 - eine parallel zur Pedalwelle verlaufende Auftrittsfläche (1a) zum Kontakt mit der Unterseite des Schuhs;
 - eine auf dem Pedal vorgesehene erste Schwenkachse (Y);
 - eine um die erste Schwenkachse (Y) verschwenkbare rückwärtige Stoßplattenklemme (7), welche eine Stoßplatteneingriffseinrichtung (4) für den Eingriff mit einem Ende (5b) der Stoßplatte (5) aufweist, bis eine einen vorgegebenen Wert übersteigende Kraft darauf einwirkt;
 - eine der rückwärtigen Stoßplattenklemme (7) quer zur Pedalwelle (2) gegenüberliegende vordere Stoßplattenklemme (6), welche zum Zusammenwirken mit der rückwärtigen Stoßplattenklemme (7) zur Ankopplung der Stoßplatte (5) an das Pedal (2) vorgesehen ist; und
 - ein Paar Begrenzungsvorsprünge (8a, 8b), welche zwischen der vorderen Stoßplattenklemme (6) und der Pedalwelle zur Begrenzung einer Verlagerung der Stoßplatte angeordnet sind;

dadurch gekennzeichnet,

daß die Begrenzungsvorsprünge (8a, 8b) um einen Abstand (W) voneinander beabstandet sind, der größer ist als eine Breite (H) entlang der Pedalwelle eines Abschnitts (5a) der Stoßplatte (5) zur Berührung der Begrenzungsvorsprünge (8a, 8b), wodurch die Stoßplatte ungehindert auf der Auftrittsfläche (1a) über den Abstand zwischen den Begrenzungsvorsprüngen und um die Stoßplatteneingriffseinrichtung (3) der vorderen Stoßplattenklemme (6) hin- und herbeweglich ist.
2. Anordnung nach Anspruch 1, **dadurch gekennzeichnet,** daß das Pedal außerdem eine der ersten Schwenkachse quer zur Pedalwelle gegenüberliegende zweite Schwenkachse aufweist, wobei die vordere Stoßplattenklemme


um die zweite Schwenkachse verschwenkbar ist.

3. Anordnung nach Anspruch 1 oder 2, **dadurch gekennzeichnet,** daß die Begrenzungsvorsprünge sich im wesentlichen senkrecht zur Auftrittsfläche erstrecken.
4. Anordnung nach einem der Ansprüche 1 bis 3, **dadurch gekennzeichnet,** daß sich die erste und die zweite Schwenkachse jeweils parallel zur Pedalwelle erstrecken.
5. Anordnung nach einem der Ansprüche 1 bis 4, **dadurch gekennzeichnet,** daß die Stoßplatteneingriffseinrichtung die Form einer Vertiefung aufweist, die in der ersten Stoßplattenklemme zum Eingriff mit der Stoßplatte ausgebildet ist.
6. Anordnung nach Anspruch 5, **dadurch gekennzeichnet,** daß die rückwärtige Stoßplattenklemme einen ersten Klemmvorsprung aufweist, der im wesentlichen parallel zur Auftrittsfläche zur vorderen Stoßplattenklemme hin verläuft und in welchem die Vertiefung ausgebildet ist, und daß die vordere Stoßplattenklemme einen zweiten Klemmvorsprung aufweist, der sich im wesentlichen parallel zur Auftrittsfläche zur hinteren Stoßplattenklemme hin erstreckt, wobei der erste Klemmvorsprung und der zweite Klemmvorsprung gegen eine Bewegung von der Auftrittsfläche weg so gesichert sind, daß die Stoßplatte an das Pedal angekoppelt ist.
7. Anordnung nach einem der Ansprüche 1 bis 6, **dadurch gekennzeichnet,** daß die Begrenzungsvorsprünge symmetrisch zu einer Mittellinie ausgerichtet sind, die senkrecht zur Pedalwelle verläuft und in die Auftrittsfläche einbezogen ist, wobei die Begrenzungsvorsprünge sich von der Mittellinie umso weiter weg erstrecken, je näher sie zur vorderen Stoßplattenklemme hin verlaufen.
8. Anordnung nach einem der Ansprüche 1 bis 7, **dadurch gekennzeichnet,** daß die rückwärtige und die vordere Stoßplattenklemme jeweils in eine Richtung federgespannt sind, in der sie mit der Stoßplatte in Eingriff kommen.
9. Anordnung nach einem der Ansprüche 1 bis 8, **dadurch gekennzeichnet,** daß die Begrenzungsvorsprünge so angeordnet sind, daß sie eine freie Bewegung der Stoßplatte entlang einer Mittellinie begrenzen, die senkrecht zur Pedalwelle verläuft und in die Auftrittsfläche

einbezogen ist.

Revendications

1. Dispositif de fixation d'une semelle portant une platine (5) à une pédale de bicyclette (1) comprenant :
 - un arbre de pédale (2) pour supporter ladite pédale en rotation ;
 - une surface d'appui (1a) orientée parallèlement à l'arbre de pédale pour venir en contact avec une semelle de ladite chaussure ;
 - un premier axe pivotant (Y) formé sur ladite pédale ;
 - un crampon arrière de platine (7) pivotant autour dudit premier axe de pivotement (Y) et comprenant un moyen de prise de platine (4) pour venir en prise avec une extrémité (5b) de ladite platine (5) jusqu'à ce qu'une force dépassant une valeur prédéterminée lui soit appliquée ;
 - un crampon avant de platine (6) opposé audit crampon arrière de platine (7) sur le travers dudit arbre de pédale (2), ledit crampon avant de platine (6) étant en coopération avec ledit crampon arrière de platine (7) pour fixer ladite platine (5) à ladite pédale (2) ; et
 - une paire de protubérances servant de limiteurs (8a, 8b) disposées entre ledit crampon avant de platine (6) et ledit arbre de pédale pour limiter le déplacement de ladite platine ;
 caractérisé en ce que lesdites protubérances servant de limiteurs (8a, 8b) sont séparées d'une distance (W) supérieure à une largeur (H) mesurée dans le sens de l'axe de pédale, sur une partie (5a) dudit crampon (5), venant en contact avec lesdites protubérances servant de limiteurs (8a, 8b), de façon à permettre ainsi à ladite platine d'osciller librement sur ladite surface d'appui (1a) sur ladite distance entre lesdites protubérances servant de limiteurs et autour du moyen de fixation de platine (3) dudit crampon avant de platine (6).
2. Dispositif selon la revendication 1, caractérisé en ce que ladite pédale comprend en outre un second axe de pivotement placé à l'opposé dudit premier axe de pivotement par rapport à l'arbre de pédale, ledit crampon avant de platine étant pivotant autour dudit second axe de pivotement.
3. Dispositif selon la revendication 1 ou 2, caractérisé en ce que lesdites protubérances servant de limiteurs s'étendent sensiblement dans une direction perpendiculaire à ladite surface d'appui.
4. Dispositif selon l'une quelconque des revendications 1 à 3, caractérisé en ce que lesdites premier et second axes de pivotement sont orientés parallèlement audit arbre de pédale.
5. Dispositif selon l'une des revendications 1 à 4, caractérisé en ce que ledit moyen de prise de platine a la forme d'un creux défini dans ledit premier crampon de platine pour venir en prise avec ladite platine.
6. Dispositif selon la revendication 5, caractérisé en ce que ledit crampon arrière de platine comprend une première protubérance d'accrochage s'étendant sensiblement parallèlement à ladite surface d'appui en direction dudit crampon avant de semelle et définissant ledit creux, et en ce que ledit crampon avant de semelle comprend une seconde protubérance d'accrochage s'étendant sensiblement dans une direction parallèle à ladite surface d'appui vers ledit crampon arrière de platine, ladite première protubérance d'accrochage et ladite seconde protubérance d'accrochage étant limitées dans leur éloignement de ladite surface d'appui, de façon à fixer ainsi ladite platine sur ladite pédale.
7. Dispositif selon l'une quelconque des revendications 1 à 6, caractérisé, en ce que lesdites protubérances servant de limiteurs sont alignées symétriquement à un axe central s'étendant perpendiculairement audit arbre de pédale, et incluses dans ladite surface d'appui, lesdites protubérances servant de limiteurs divergeant en s'éloignant dudit axe quand lesdites protubérances servant de limiteurs s'étendent en direction dudit crampon avant de platine.
8. Dispositif selon l'une quelconque des revendications 1 à 7, caractérisé en ce que lesdits crampons arrière et avant de platine sont sollicités par des ressorts dans des directions de prise de ladite platine.
9. Dispositif selon l'une quelconque des revendications 1 à 8, caractérisé en ce que lesdites protubérances servant de limiteurs sont disposées pour limiter le libre mouvement de ladite platine le long d'un axe central orienté perpendiculairement audit arbre de pédale, et incluses dans ladite surface d'appui.






FIG.2




FIG.3




FIG. 4 (PRIOR ART)